

Hot water & steam

T-350 AA

STEAM 7 BAR (100 PSI) / HOT

WATER 15 BAR (225 PSI)

EXCEEDS BS 5122/A TYPE 2



TUBE	BLACK EPDM
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS
COVER	BLACK EPDM - HEAT, ABRASION AND OZONE RESISTANT
APPLICATION	SATURATED STEAM AND HOT WATER DELIVERY IN GENERAL INDUSTRIAL APPLICATIONS.
TEMPERATURE	-40°C +165°C (-40°F +330°F)
BRAND TEXT	ALFAGOMMA -ITALY- T-350 7 BAR (100 PSI) STEAM 165°C (330°F)
BRAND TYPE	RED LETTERS
NOTE	
APPROVALS	
SAFETY FACTOR	ACCORDING TO BS 5122/A TYPE 2

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
350AA010203ND0	10	3/8	20	5	290	7	100			61	61
350AA013233ND0	13	1/2	23	5	370	7	100			20/61	61
350AA016263ND0	16	5/8	26	5	430	7	100			61	61
350AA019313ND0	19	3/4	31	6	610	7	100			20/40	40
350AA025373ND0	25	1	37	6	750	7	100			20/40	40
350AA030443ND0	30	1 3/16	44	7	900	7	100			40	40
350AA032463ND0	32	1 1/4	46	7	950	7	100			20/40	40
350AA038523ND0	38	1 1/2	52	7	1100	7	100			20/40	40
350AA040543ND0	40	1 9/16	54	7	1150	7	100			40	40
350AA051673ND0	51	2	67	8	1700	7	100			20/40	40